

KM 7699 FR

Induction hob with onset controls
with TempControl for perfect frying results



- Intuitive quick selection via number sequences – Smart Select
- 5 cooking zones incl. 1 PowerFlex area and 1 TempControl zone
- A width of 942 mm with stainless steel frame for surface installation
- Shortest heating-up times – TwinBooster
- Communication with the hood – automatic function Con@ctivity

EAN: 4002516338796 / Material number: 11515550 / Old Material Number: 26769900GB

Heating type	
Heating type	Induction
Construction type	
Independent of cooker	•
Design	
Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless steel frame	•
Surface-mounted installation	•
Cooking zone details	
Number of cooking zones	5
Number of cooking areas	1
Maximum number of pans	5
PowerFlex cooking zones	
No.	2
Type	PowerFlex-Kochzone
Size in mm	150x230
Max. rating in W	2.10
Max. Booster power rating in W	3.00
Max. TwinBooster power rating in W	3650
1st cooking zone/cooking area	
Position	front left
Type	Dual-circuit ring
Size in mm	100-160 mm
Max. rating in W	1400
Max. Booster power rating in W	1700
Max. TwinBooster power rating in W	2200
2nd cooking zone/cooking area	
Position	rear left
Type	TempControl cooking zone
Size in mm	160-230 mm
Max. rating in W	2300
Max. Booster power rating in W	3000
Max. TwinBooster power rating in W	3650
3rd cooking zone/cooking area	
Position	rear centre
Type	Dual-circuit ring
Size in mm	180-280
Max. rating in W	2600
Max. Booster power rating in W	3000
Max. TwinBooster power rating in W	3650
4th cooking zone/cooking area	
Position	right
Type	PowerFlex bridge
Max. rating in W	3400
Max. Booster power rating in W	4800
Max. TwinBooster power rating in W	7300
User convenience	
Networking with Miele@home	•
Automatic function Con@ctivity 3.0	•

KM 7699 FR

Induction hob with onset controls
with TempControl for perfect frying results



EAN: 4002516338796 / Material number: 11515550 / Old Material Number: 26769900GB

Pan and pan size recognition	•
Display colour	Yellow
Operation via sensor controls	Smart Select
Auto heat-up	•
Permanent pan recognition	•
Recall function	•
TempControl	•
Safety switch-off	•
Individual setting options (e.g. buzzers)	•
Stop & Go function	•
Minute minder	•
Keeping warm	•
Keeping warm plus	•
Efficiency and sustainability	
Power rating in off mode in W	0.5
Power rating in standby mode in W	1.0
Power rating in networked standby in W	2.0
Time until automatic switch to off mode in min	20
Time until automatic switch to standby in min	20
Time until automatic switch to networked standby in min	20
Cleaning convenience	
Easy to clean ceramic glass	•
Wipe protection	•
Safety	
Safety switch-off	•
Lock function	•
System lock	•
Integrated cooling fan	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions in mm (width)	942
Dimensions in mm (height)	52
Casing height incl. connection box in mm	45
Dimensions in mm (depth)	526
Cutout dimensions in mm (width) with surface-mounted installation	916
Cutout dimensions in mm (depth) with surface-mounted installation	500
Weight in kg	16
Total rated load in kW	11.00
Length of supply lead in m	1.4
Voltage in V	230
Frequency in Hz	50-60
Accessories supplied	
Number of mains cables with plug	Yes

KM 7699 FR
Induction hob with onset controls
with TempControl for perfect frying results

KM 7699 FR (installtion drawing)

1) Front , 2) Mains connection box with mains connection
cable, L = 1440 mm, are enclosed loosely