

KM 7474 FR Induction hob with onset controls with PowerFlex cooking area for maximum power output

Heating type Heating type



- Quick selection via numerical keybank – ComfortSelect
- 4 cooking zones incl. 1 high-power PowerFlex cooking area
- A width of 806 mm with stainless steel frame for surface installation
- Shortest heating-up times TwinBooster
- Communication with the hood automatic function Con@ctivity

Heating type	Induction
Construction type	
Independent of cooker	•
Design	
Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless steel frame	•
Surface-mounted installation	•
Cooking zone details	
Number of cooking zones	4
Number of cooking areas	1
Maximum number of pans	4
PowerFlex cooking zones	
No.	2
Туре	PowerFlex cooking zone
Size in mm	150x230
Max. rating in W	2.10
Max. Booster power rating in W	3.00
Max. TwinBooster power rating in W	3650
1st cooking zone/cooking area	
Position	front left
Туре	Dual-circuit ring
Max. Booster power rating in W	3000
Max. rating in W	2300
2nd cooking zone/cooking area	2000
Position	rear centre
Туре	Dual-circuit ring
Size in mm	100-160 mm
Max. Booster power rating in W	1700
Max. rating in W	1400
Max. TwinBooster power rating in W	2200
3rd cooking zone/cooking area	2200
Position	right
Туре	PowerFlex bridge
Size in mm	230x390
Max. Booster power rating in W	4800
Max. rating in W	3400
Max. TwinBooster power rating in W	7300
User convenience	7500
Miele@home	•
Operation via sensor controls	ComfortSelect
Automatic function Con@ctivity	
	•
Pan and pan size recognition	
Display colour	Yellow
Auto heat-up	•
Permanent pan recognition	•
Keeping warm	•
Stop & Go function	•
Recall function	•

EAN: 4002516149262 / Material number: 11144040 / Old Material Number: 26747400GB

Induction



KM 7474 FR Induction hob with onset controls with PowerFlex cooking area for maximum power output



EAN: 4002516149262 / Material number: 11144040 / Old Material Number: 26747400GB

Minute minder	•
Safety switch-off	•
Individual setting options (e.g. buzzers)	•
Efficiency and sustainability	
Power rating in off mode in W	0.5
Power rating in standby mode in W	1.0
Power rating in networked standby in W	2.0
Time until automatic switch to off mode in min	20
Time until automatic switch to standby in min	20
Time until automatic switch to networked standby in min	20
Cleaning convenience	
Easy to clean ceramic glass	•
Safety	
Safety switch-off	•
Lock function	•
System lock	•
Integrated cooling fan	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions (W x H x D) in mm	52 x 806 x 526
Dimensions in mm (width)	806
Dimensions in mm (height)	52
Dimensions in mm (depth)	526
Cutout dimensions in mm (width) with surface-mounted installation	780
Casing height incl. connection box in mm	45
Cutout dimensions in mm (depth) with surface-mounted installation	500
Weight in kg	12
Total rated load in kW	7.30
Length of supply lead in m	1.4
Voltage in V	230
Frequency in Hz	50-60
Accessories supplied	
Number of mains cables with plug	Yes



KM 7474 FR Induction hob with onset controls with PowerFlex cooking area for maximum power output



KM 7474 FR (installation drawings) 1) Front, 2) Mains connection box with mains connection cable, L = 1440 mm