

WED385 WCS PWash&Steam&9kg W1 front-loader washing machine:

A -20 %* I 9 kg I 1400 rpm I SteamCare I QuickPowerWash I Miele@home



- Tested for 20 years of perfect laundry care*
- Save even more energy with A -20 %**
- SteamCare reduces ironing time by up to 50 % and freshens up your clothes
- QuickPowerWash ensures fast, efficient results in just 49 minutes***
- Complete app control of your washing machine with Miele@ home****
- * During the development phase of the W1 washing machine series, Miele tested models and core components in 5000 wash loads (= 5 wash loads per week for 50 weeks per year) in various programmes. More: miele.com/20years
- ** 20 % more economical than the threshold value (52) for energy efficiency class A.
- *** This applies to all Miele washing machines that enable the process and machine-related parameters presented in the summary of the WL 1110/18 test report to be implemented.
- **** Additional digital offer from Miele & Cie. KG. All smart applications are made possible with the Miele@home system. The range of functions can vary depending on the model and the country.



EAN: 4002516865759 / Material number: 12721260 / Old Material Number: 11ED3851GB

Construction type	
Suitable for stacking	•
Side-by-side	•
Slot-in	•
Can be built-under	•
Door hinge	right
Model	
Product brand	W1 Chrome Edition
Front-loader	•
Spinning	
Max. spin speed	1400
Rinse hold	•
Without spin function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Graphite grey PearlFinish
Rotary selector colour	Lotus White
Control panel version	Straight
Control type	Rotary control
Display	DirectSensor white,
Display	7 segment
Cleaning performance	
Innovative PowerWash technology	•
CapDosing portioned dispensing	•
Gentle laundry care	
Honeycomb drum	•
Load in kg	9.0
User convenience	
Networking with Miele@home	•
Delay start up to 24 hours	•
Time left display	•
AutoClean detergent drawer	•
AddLoad	•
Efficiency and sustainability	
Energy efficiency class (A–G)	A
More economical than the threshold value (52) for energy	20%
efficiency class A	
Weighted energy consumption per 100 operating cycles for the wash cycle in kWh	40
Weighted water consumption per cycle in I	50
Spin efficiency class	В
Acoustic airborne noise emission class (spin cycle)	А
Sound emissions during spin cycle in dB(A) re 1 pW	72
Duration of the "ECO 40–60" programme at nominal capacity	229
Power rating in off mode in W	0.30
Power rating in networked standby in W	0.60
Low temperature wash "Cold" and "20 °C"	•



WED385 WCS PWash&Steam&9kg W1 front-loader washing machine:

A -20 %* I 9 kg I 1400 rpm I SteamCare I QuickPowerWash I Miele@home



EAN: 4002516865759 / Material number: 12721260 / Old Material Number: 11ED3851GB


Flow meter Foam sensing ProfiEco motor Wash programmes QuickPowerWash Cottons (coloureds) Minimum iron Delicates Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (width) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth in kg Total rated load in kW Voltage in V EVA Fuse rating in A 13	Automatic load control	•
ProfiEco motor Wash programmes QuickPowerWash Cottons (coloureds) Minimum iron Delicates Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Well and in the selection of the selection o	Flow meter	•
Wash programmes QuickPowerWash • Cottons (coloureds) • Minimum iron • Delicates • Shirts • Woollens (hand-washable) • Express 20 • Dark garments / Denim • Freshen up (steam) • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water protection system Safety lock • PIN-Code • Optical interface • Technical data • Dimensions in mm (width) 596 Dimensions in mm (height) 643 Appliance depth in mm with opened door 1054 Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW </td <td>Foam sensing</td> <td>•</td>	Foam sensing	•
QuickPowerWash Cottons (coloureds) Minimum iron Delicates Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (depth) Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Peditors • Safety Safety lock PIN-Cade Optical interface Technical data Dimensions in mm (depth) Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V 220-240	ProfiEco motor	•
Cottons (coloureds) Minimum iron Delicates Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Voltage in V P	Wash programmes	
Minimum iron Delicates Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Fechnical data Dimensions in mm (width) Dimensions in mm (depth) Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V PExpress 20 P. Code P. Cod	QuickPowerWash	•
Delicates Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Vale Code Popark garments / Presented (Presented Presented Pre	Cottons (coloureds)	•
Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (depth) Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Poparis (Appliance depth appliance) Poparis (Appliance depth appliance) Poparis (Appliance) Poparis (A	Minimum iron	•
Express 20	Delicates	•
Express 20	Shirts	•
Dark garments / Denim Freshen up (steam) Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (depth) Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V 200-240	Woollens (hand-washable)	•
Freshen up (steam) • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water control-System Safety lock • PIN-Code • Optical interface • Technical data - Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW 2:10-2:40 Voltage in V 220-240	Express 20	•
Drain / Spin ECO 40-60 Washing extras Short Pre-wash Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (width) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V 200-240	Dark garments / Denim	•
ECO 40-60 Washing extras Short Pre-wash Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Appliance depth of the state of the stat	Freshen up (steam)	•
Washing extras Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water protection system Safety lock • PIN-Code • Optical interface • Technical data Dimensions in mm (width) Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1054 Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240	Drain / Spin	•
Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V 220-240	ECO 40-60	•
Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V 220-240	Washing extras	
Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V 20-240	Short	•
Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Voltage in V	Pre-wash	•
Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Vatercontrol-System * Watercontrol-System * * * * * * * * * * * * *	Water plus	•
Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Watercontrol-System Watercontrol-System 6 6 0 4 6 6 6 6 6 7 8 8 8 8 7 2 2 7 7 8 8 7 8 8 8 7 8 8 7 8 8	Additional rinse cycle	•
Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Voltage in V Watercontrol-System Watercontrol-System 60 64 64 70 85 80 80 70 210-2.40	Pre-ironing with steam	•
Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V Watercontrol-System 6 64 6 80 210-2.40	Buzzer	•
Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V • • • 1054 80 7012-2.40 220-240	Safety	
PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V • • • • • • • • • • • • • • • • • •	Water protection system	Watercontrol-System
Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V • S96 643 A50 A50 A643 A90 A90 A90 A90 A90 A90 A90 A9	Safety lock	•
Technical data Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1054 Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240	PIN-Code	•
Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1054 Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240	Optical interface	•
Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Appliance depth excluding door (for building-under) in mm Weight in kg Total rated load in kW Voltage in V 250-240	Technical data	
Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1054 Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240	Dimensions in mm (width)	596
Appliance depth in mm with opened door 1054 Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240	Dimensions in mm (height)	850
Appliance depth excluding door (for building-under) in mm 600 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240	Dimensions in mm (depth)	643
Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240	Appliance depth in mm with opened door	1054
Total rated load in kW 2.10-2.40 Voltage in V 220-240	Appliance depth excluding door (for building-under) in mm	600
Voltage in V 220-240	Weight in kg	80
	Total rated load in kW	2.10-2.40
Fuse rating in A 13	Voltage in V	220-240
	Fuse rating in A	13
Frequency in Hz 50	Frequency in Hz	50
Length of supply lead in m 2	Length of supply lead in m	2




WED385 WCS PWash&Steam&9kg

W1 front-loader washing machine:


A -20 %* | 9 kg | 1400 rpm | SteamCare | QuickPowerWash | Miele@home




W1 installation drawing, slanted facia or straight facia,



W1 drawing, slanted facia or straight facia, measures in



W1 drawing, slanted facia or straight facia, measures in



W1 drawing, slanted facia or straight facia, measures in $\,$ mm $\,$